



- NOTES**
1. Dowels saw cut from hot rolled steel bar per ASTM A36 to within 3/16" of specified length.
 2. Side frame supports fabricated from 1/4" diameter cold drawn wire per ASTM A108 grade 1010 - 1020.
 3. Lightly grease full length of dowels or specify factory debonded baskets from PNA Construction Technologies, Inc.
 4. Assemblies manufactured so that they stack on top of each other for transportation and remain stable under concrete placement.
 5. End round dowel cannot be placed closer than 12" to the joint intersection.
 6. Round Dowel Basket assembly as manufactured by PNA Construction Technologies, Inc. (800) 542-0214

SHEET#

RDB-1

PNA Round Dowel Basket Isometric

DATE August 2007

SCALE NTS

JOB #

DRAWN BY

APPROVED



© 2007 PNA Construction Technologies

www.pna-inc.com

Nine Dunwoody Park, Suite 111
Atlanta, GA 30338

(800) 542-0214
fax (770) 455-6803

©PNA Construction Technologies, Inc. All rights reserved. Diamond Dowel®, Armo-Edge®, Load Plate Basket® and PD3 Basket® are registered trademarks and Hydracure™ and Square™ Dowel Clip are trademarks of PNA Construction Technologies, Inc. Products shown may be covered by one or more of U.S. patents #6,775,952, #6,354,760, #5618125; Great Britain patent #1034340; Mexico patent #22942; New Zealand patent #504785; India patent #203607 and other pending patents.