



NOTES

1. PNA Load Plates saw cut from hot rolled bar per ASTM A36 to within 3/16".
2. PNA Load Plate clips with compressible side material fitted to the free end of the Load Plate and extending to within $\pm 3/16"$ of 2/3 the bar length.
3. Side frame supports fabricated from 1/4" diameter cold drawn wire per ASTM A108 grade 1010 - 1020.
4. Assemblies manufactured so that they stack on top of each other for transportation and remain stable under concrete placement.
5. End of load plate dowel is placed up to 6" from joint intersection.
6. Load Plate Basket™ assembly as manufactured by PNA Construction Technologies, Inc. (800) 542-0214.

SHEET#

LPB-3

Load Plate Basket™ Assembly at Joint Intersection

DATE August 2007

SCALE NTS

JOB #

DRAWN BY

MSS

APPROVED

©PNA Construction Technologies, Inc. All rights reserved. Diamond Dowel®, Armo-Edge®, Load Plate Basket® and PD3 Basket® are registered trademarks and Hydracure™ and Square™ Dowel Clip are trademarks of PNA Construction Technologies, Inc. Products shown may be covered by one or more of U.S. patents #6,775,952, #6,354,760, #5618125; Great British patent #1034340; Mexiko patent #22942; New Zealand patent #504785; India patent #203607 and other pending patents.

© 2007 PNA Construction Technologies



www.pna-inc.com

Nine Dunwoody Park, Suite 111 (800) 542-0214
 Atlanta, GA 30338 fax (770) 455-6803