



**NOTES:**

1. PD<sup>3</sup> Basket® plate dowels are specified to ensure the following cross-sectional areas of steel at the joint: 2"x3/8", 2-1/2"x1/2" and 2-1/2"x3/4".
2. The length of the PD<sup>3</sup> Basket® plate dowel is specified as a 12" or 8" length to deliver an eight- or four- inch saw-cut installation construction tolerance.
3. Tapered plate dowels plasma cut from hot rolled bar certified to meet ASTM A36 standards to within 3/16" of specified length.
4. The tapered plate dowels are coated with a DOT approved debonding agent Tectyl® 506. The coating is uniformly applied without excessive drips or thickness.
5. Side frame supports fabricated from 1/4" diameter cold drawn wire certified to meet ASTM A108 grade 1010-1020 standards.
6. Assemblies manufactured so that they stack on top of each other for transportation and remain stable under concrete placement.
7. End tapered plate dowel can be placed up to six inches of joint intersection.
8. PD<sup>3</sup> Basket® assembly as manufactured by PNA Construction Technologies, Inc. (800) 542-0214.

SHEET#  
**PD3-1**

**PD<sup>3</sup> Basket® Assembly - Isometric**

DATE **August 2007**

SCALE **NTS**

JOB #

DRAWN BY

APPROVED

© 2008 PNA Construction Technologies, Inc.



www.pna-inc.com

Nine Dunwoody Park, Suite 111 (800) 542-0214  
Atlanta, GA 30338 fax (770) 455-6803

©PNA Construction Technologies, Inc. All rights reserved. Diamond Dowel®, Armor-Edge®, Load Plate Basket® and PD3 Basket® are registered trademarks and HydraCure™ and Square™ Dowel Clip are trademarks of PNA Construction Technologies, Inc. Products shown may be covered by one or more of U.S. patents #6,775,952, #6,354,760, #5618125; Great Britain patent #1034340; Mexico patent #22942; New Zealand patent #504785; India patent #203607 and other pending patents.